

# MAZIC K-1560

MAZIC K-1560 is a countertop kiosk equipped with dual side monitors. Store customers can self-serve the 15.6-inch monitor or assist with payment at the store counter. This new concept compact kiosk will provide customers with a fresh shopping experience.



## MAZIC K-1560 Features



| Dual screens



| Screen Tilting



| OS Support



| Screen orientation

# MAZIC K-1560 System

	MAZIC® K-1560 AP	MAZIC® K-1560 AN	MAZIC® K-1560 EL	MAZIC® K-1560 A2
<b>System</b>				
	Windows			Android
Processors	Intel® Core™ i5-1235U Processor 12M Cache, up to 4.40 GHz Intel® Core™ i3-1215U Processor 10M Cache, up to 4.40 GHz	Intel® Processor N97 6M Cache, up to 3.60 GHz	Intel® Celeron® Processor J6412 1.5M Cache, up to 2.60 GHz	RK3399 Dual-core Cortex-A72 up to 1.8GHz Quad-core Cortex-A53 up to 1.4GHz
Chipset	Intel® Alder Lake-P	Intel® Alder Lake-N	Intel® Elkhart Lake	
Memory	4GB Standard, DDR4 3200 MT/s, Socket 1 x SODIMM (Max. 32GB)	4GB Standard, DDR4 3200 MT/s, Socket 1 x SODIMM (Max. 16GB)	4GB Standard, DDR4 3200 MT/s, Socket 1 x SODIMM (Max. 32GB)	4GB Standard, LPDDR4, On-board
Storage	1. Form Factor NVMe M.2 2242-D2-M (No capacity limit.) 2. Mountable quantity: Up to 2 units can be installed. * Factory Default : NVMe M.2 2242 128GB x 1			eMMC 32GB, On-board (Max.64GB)
Operating Systems	Windows 10 version 21H1 or higher		Windows 10 IoT Enterprise LTSC	Android 9.0/ 12
Audio	HD Audio Codec			

## MAZIC K-1560



Superior performance



Powerful performance



Android RK3399

# MAZIC K-1560 Display | Interface

15.6"



15.6"



	MAZIC® K-1560 AP	MAZIC® K-1560 AN	MAZIC® K-1560 EL	MAZIC® K-1560 A2
<b>Display</b>				
Type	15.6" TFT LCD , LED Backlight			
Resolution	1080 x 1920, 1920x1080 (Dual Monitor)			
Brightness	300 cd/m <sup>2</sup> (typ.)			
Touchscreen	Projected Capacitive Touch			
Response	25 ms			
Contrast Ratio	1000 (typ.)			
<b>Interface</b>				
USB	External 4 (USB 3.0 x 2, USB2.0 x 2) Internal 4 (USB 2.0 x 4 (Reserved for MSR/SCR, Printer, Scanner, NFC))			
Serial	External 2 (COM1,COM 2( RJ-45, Full Signal)) Internal 5 (COM3~4 Reserved for mini-DP1/2) (COM5 Reserved for Printer) (COM6 Tx/Rx only, Reserved for SCR) (COM7 MDS(Motion Detection Sensor))			
LAN	Gigabit Ethernet x 1, RJ-45			
WiFi/BT	-			Bluetooth (V5.0)+ WLAN (802.11 a/b/g/n, 2.4G/5G) combo module, On-board
Power DC-IN	3 Pin DIN Jack			
<b>Power</b>				
Power Supply	Adaptor 24V, 6.35A			
<b>Pedestal</b>				
Material	Galvanized Steel Plate			
Material Thickness	1.2T			
Component Access	-			

## MAZIC K-1560 Physical & Environmental

	MAZIC® K-1560 AP	MAZIC® K-1560 AN	MAZIC® K-1560 EL	MAZIC® K-1560 A2
<b>Physical &amp; Environmental</b>				
Operating Temperature	0 °C ~ 50 °C at 10% to 90% Humidity			
Storage Temperature	-20 °C ~ 60 °C at 10% to 90% Humidity			
Dimensions (W x D x H)	System: (W)398 x (D)239 x (H)600 (mm), (W)15.66 x (D)9.4 x (H)23.62 (in) Base Plate: (W)234 x (D)195 x (H)3 (mm), (W)9.21 x (D)7.68 x (H)0.11 (in)			
Packing Dimensions (W x D x H)	System: (W)350 x (D)316 x (H)638 (mm), (W)13.78 x (D)12.44 x (H)25.11 (in)			
Net Weight	System (Single monitor): 8,644g, 19.05 lbs System (Dual monitor): 11,080g, 24.42 lbs Baseplate: 1,020g, 2.24 lbs			
Packing Weight	System (Single monitor): 11,564g, 25.49 lbs System (Dual monitor): 14,000g, 30.86 lbs			
Certification	CE,FCC,KC			
Color	White			

## MAZIC K-1560 Options

	MAZIC® K-1560 AP	MAZIC® K-1560 AN	MAZIC® K-1560 EL	MAZIC® K-1560 A2
<b>Options</b>				
Storage	-			
Built-in Printer	3" Jam-Free Thermal, Max. 250mm/s, Auto Cutter (Interface : Serial, USB)			
Barcode Scanner	1D, 2D Barcode			
Camera	5M USB Interface (With Mic, Internal) (Factory Option)			
Magnetic Stripe Reader	Comply with ISO 7811, Support 1 & 2 & 3 Track			
Smart Card Reader	EMV Level 1			
NFC Reader	MIFARE, FeliCa, ISO/IEC 14443A, ISO/IEC 14443B, ISO/IEC 15693			
Wall Mount Kit	-			
Speaker	1 x 5W (Mono)			
WiFi	M.2 for WiFi/BT			-
Bracket Payment	EFT Terminal Bracket option			

\*Specifications may change without prior notice.

# MAZIC K-2150

MAZIC K-2150 has a compact and aesthetic design that can be installed on a table and used as a natural interior item. It is a kiosk that can be installed with a 21.5-inch display without compromising the aesthetics of the store and has excellent functionality.



## MAZIC K-2150 Features



Counter-Top



Slim & Sleek



OS Support



Options

# MAZIC K-2150 System

	MAZIC® K-2150 AP	MAZIC® K-2150 AN	MAZIC® K-2150 EL	MAZIC® K-2150 A2
<b>System</b>				
	Windows			Android
Processors	Intel® Core™ i5-1235U Processor 12M Cache, up to 4.40 GHz Intel® Core™ i3-1215U Processor 10M Cache, up to 4.40 GHz	Intel® Processor N97 6M Cache, up to 3.60 GHz	Intel® Celeron® Processor J6412 1.5M Cache, up to 2.60 GHz	RK3399 Dual-core Cortex-A72 up to 1.8GHz Quad-core Cortex-A53 up to 1.4GHz
Chipset	Intel® Alder Lake-P	Intel® Alder Lake-N	Intel® Elkhart Lake	
Memory	4GB Standard, DDR4 3200 MT/s, Socket 1 x SODIMM (Max. 64GB)	4GB Standard, DDR4 3200 MT/s, Socket 1 x SODIMM (Max. 16GB)	4GB Standard, DDR4 3200 MT/s, Socket 1 x SODIMM (Max. 32GB)	4GB Standard, LPDDR4, On-board
Storage	1. Form Factor NVMe M.2 2242-D2-M (No capacity limit.) 2. Mountable quantity: Up to 2 units can be installed. * Factory Default : NVMe M.2 2242 128GB x 1			eMMC 32GB, On-board (Max.64GB)
RAID	RAID 0,1			
Operating Systems	Windows 10 version 21H1 or higher		Windows 10 IoT Enterprise LTSC	Android 9.0/ 12
Audio	HD Audio Codec			

## MAZIC K-2150



Superior performance



Powerful performance



Android RK3399

# MAZIC K-2150 Display | Interface

21.5"



	MAZIC® K-2150 AP	MAZIC® K-2150 AN	MAZIC® K-2150 EL	MAZIC® K-2150 A2
<b>Display</b>				
Type	21.5" TFT LCD, LED Backlight			
Resolution	1080 x 1920			
Brightness	250 cd/m <sup>2</sup> (typ.)			
Touchscreen	Projected Capacitive Touch			
Response	20 ms			
Contrast Ratio	3000 (typ.)			
<b>Interface</b>				
USB	External 6 (USB 3.0 x 2, USB 2.0 x 4) Internal 3 (USB 2.0 x 3 (Reserved for MSR, SCR, Printer))			
Serial	External 2 (COM10, COM 11( RJ-45, Full Signal)) Internal 3 (COM7 MDS(Motion Detection Sensor)) (COM12 Tx/Rx only, Reserved for SCR) (COM13 Reserved for Printer)		External 2 (COM 1, COM 2( RJ-45, Full Signal)) Internal 3 (COM 7 MDS (Motion Detection Sensor)) (COM 6 Tx/Rx only, Reserved for SCR) (COM5 Reserved for Printer)	
LAN	Gigabit Ethernet x 1, RJ-45			
WiFi/BT	-		Bluetooth (V5.0)+ WLAN (802.11 a/b/g/n, 2.4G/5G) combo module, On-board	
Power DC-IN	3 Pin DIN Jack			
<b>Power</b>				
Power Supply	Adaptor 24V, 6.35A			
<b>Pedestal</b>				
Material	Galvanized Steel Plate			
Material Thickness	1.2T			
Component Access	-			

## MAZIC K-2150 Physical & Environmental

	MAZIC® K-2150 AP	MAZIC® K-2150 AN	MAZIC® K-2150 EL	MAZIC® K-2150 A2
<b>Physical &amp; Environmental</b>				
Operating Temperature	0 °C ~ 60 °C at 10% to 90% Humidity			
Storage Temperature	-20 °C ~ 60 °C at 10% to 90% Humidity			
Dimensions (W x D x H)	System: (W)333 x (D)200 x (H)750 (mm), (W)13.11 x (D)7.87 x (H)29.53 (in) Pedestal: (W)333 x (D)200 x (H)892 (mm), (W)12.95 x (D)7.87 x (H)35.11 (in) Baseplate: (W)440 x (D)310 x (H)8 (mm), (W)17.32 x (D)12.20 x (H)0.31 (in)			
Packing Dimensions (W x D x H)	System: (W)820 X (D)280 X (H)420 (mm), (W)32.28 x (D)11.02 x (H)16.53 (in) Pedestal (with baseplate): (W)950 X (D)270 X (H)420 (mm), (W)37.4 x (D)10.62 x (H)16.53 (in)			
Net Weight	System: 10,560g, 23.28 lbs Pedestal: 11,545g, 25.45 lbs Baseplate: 8,045g, 17.73 lbs			
Packing Weight	System: 13,610g, 30.00 lbs Pedestal (with baseplate): 23,580g, 51.98 lbs			
Certification	CE, FCC, KC			
Color	White			

## MAZIC K-2150 Options

	MAZIC® K-2150 AP	MAZIC® K-2150 AN	MAZIC® K-2150 EL	MAZIC® K-2150 A2
<b>Options</b>				
Storage	-			
Built-in Printer	3" Jam-Free Thermal, Max. 250mm/s, Auto Cutter (Interface : Serial, USB)			
Barcode Scanner	1D, 2D Barcode			
Camera	5M USB Interface (With Mic, Internal) (Factory Option)			
Magnetic Stripe Reader	Comply with ISO 7811, Support 1 & 2 & 3 Track			
Smart Card Reader	EMV Level 1			
NFC Reader	MIFARE, FeliCa, ISO/IEC 14443A, ISO/IEC 14443B, ISO/IEC 15693			
Wall Mount Kit (W x H x D)	(W)280 x (D)200 x (H)214(mm), (W)11.02 x (D)7.87 x (H)8.42			
Speaker	1 x 5W (Mono)			
WiFi	M.2 for WiFi/BT			-
Bracket Payment	EFT Terminal Bracket option			

\*Specifications may change without prior notice.